

Product Comparison Table for Low-Mercury (Green) Lamps

Model	No. of Lamps	Lumen Output	Types of Lamps Operated	Features
B94G	1 lamp	300 - 750 lm	13-42 W (4-pin) twin, quad or triple twin-tube	ELC*; Compatible with low-mercury (green) lamps; Suitable for damp locations and for sealed & gasketed fixtures; UL Listed
B94CG	1 lamp	300 - 750 lm	13-42 W (4-pin) twin, quad or triple twin-tube	ELC; Compatible with low-mercury (green) lamps; Suitable for damp locations; UL Listed
B84CG	1 lamp	Up to 1250 lm	13-42 W (4-pin) twin, quad or triple twin-tube; 22-40 W T5 circline; or 18-39 W long compact	ELC; Compatible with low-mercury (green) lamps; Suitable for damp locations; UL Listed
B4CFG	1 lamp	Up to 1250 lm	13-42 W (4-pin) twin, quad or triple twin-tube; 22-40 W T5 circline; or 18-39 W long compact	ELC; Compatible with low-mercury (green) lamps; Suitable for damp locations and for sealed & gasketed fixtures; UL Listed / CSA Certified
B4CF1	1 lamp	Up to 1250 lm	13-42 W (4-pin) twin, quad or triple twin-tube; 22-40 W T5 circline; or 18-39 W long compact	ELC; Compatible with low-mercury (green) lamps; Suitable for extended temperatures; Suitable for damp locations and for sealed & gasketed fixtures; UL Listed / CSA Certified
B4CF2	1 lamp	Up to 1250 lm	13-42 W (4-pin) twin, quad or triple twin-tube; 22-40 W T5 circline; or 18-39 W long compact	ELC; Compatible with low-mercury (green) lamps; Suitable for extended temperatures; Suitable for damp locations; UL Listed / CSA Certified
B4CF3	1 lamp	Up to 1250 lm	13-42 W (4-pin) twin, quad or triple twin-tube; 22-40 W T5 circline; or 18-39 W long compact	ELC; Compatible with low-mercury (green) lamps; Suitable for extended temperatures; Suitable for damp locations and for sealed & gasketed fixtures; UL Listed / CSA Certified
B75C	1 lamp	600 - 1300 lm	32-70 W (4-pin) triple twin-tube	ELC; Compatible with low-mercury (green) lamps; Suitable for damp locations; UL Listed
LP500	1 lamp	400 - 700 lm	21-54 W (2'-4') T5 or 32 W (4') T8	ELC; Compatible with low-mercury (green) lamps; Suitable for damp locations and for sealed & gasketed fixtures; Low Profile; UL Listed
LP550	1 lamp	390 - 700 lm	One 14-54 W (2'-4') standard or high output T5 or T8; 17-55 W (2'-5') T8; 36-55 W (4-pin) long compact; or 22-55 W T5 circline	ELC; Compatible with low-mercury (green) lamps; Suitable for damp locations and for sealed & gasketed fixtures; Low Profile; UL Listed
LP600	1 lamp	600 - 1325 lm	One 14-54 W (2'-4') standard or high output T5 or T8; 17-55 W (2'-5') T8; 36-55 W (4-pin) long compact; or 22-55 W T5 circline	ELC; Compatible with low-mercury (green) lamps; Suitable for damp locations and for sealed & gasketed fixtures; Low Profile; UL Listed / CSA Certified
LP600STU	1 lamp	600 - 1325 lm	One 14-54 W (2'-4') standard or high output T5 or T8; 17-55 W (2'-5') T8; 36-55 W (4-pin) long compact; or 22-55 W T5 circline	ELC; Compatible with low-mercury (green) lamps; Universal Input; Suitable for damp locations and for sealed & gasketed fixtures; Self-Testing; Low Profile; UL Listed / CSA Certified

* ELC products have a patented circuit that delays the AC ballast operation for approximately 3 seconds to prevent false tripping of the AC ballast end-of-lamp-life shutdown circuits.