

# REDiTEST<sup>®</sup> Series Product Comparison



Model	No. of Lamps	High Lumen Output	Types of Lamps Operated	Features
<b>B30ST</b>	1 or 2 lamps	Up to 3500 lm	One or two 17-215 W (2'-8') T8s - T12s or (4-pin) long compacts; one 21-54 W (2'-4') standard or high output T5	ELC*; Self-Testing; Suitable for damp locations; UL Listed / CSA Certified
<b>B50ST</b>	1 or 2 lamps	Up to 1400 lm	One or two 17-215 W (2'-8') T8s - T12s; (4-pin) long compacts	ELC; Self-Testing; UL Listed / CSA Certified
<b>LP600STU</b>	1 lamp	Up to 1325 lm	One 14-54 W (2'-4') standard or high output T5; 17-55 W (2'-5') standard or high output T8; 36-55 W long compact; 22-55 W high output T5 circline	ELC; Compatible with low-mercury (green) lamps; Universal Input; Suitable for damp locations and sealed & gasketed fixtures; Self-Testing; Low-Profile; UL Listed / CSA Certified
<b>B74CST</b>	1 or 2 lamps	Up to 1350 lm	One or two 17-215 W (2'-8') T8s - T12s; (4-pin) compacts or long compacts	ELC; Suitable for damp locations; UL Listed

\* ELC products have a patented circuit that delays the AC ballast operation for approximately 3 seconds to prevent false tripping of the AC ballast end-of-lamp-life shutdown circuits.