

Universal Input Voltage - 120 through 277 VAC Product Summary



Model	No. of Lamps	Lumen Output	Types of Lamps Operated	Features
LP600STU	1 lamp	600 - 1325 lm	One 14 -54 W (2'-4') T5 bipin, 22-40 W T5 circular, 36-55 W (4-pin) long compact or 17-55 W (2'-5') T8 bipin	ELC*; Compatible with low-mercury (green) lamps; Suitable for damp locations and sealed & gasketed fixtures; Self-Testing; Low-Profile; UL Listed / CSA Certified
B50U	1 or 2 lamps	Up to 1400 lm	One 17-215 W (2'-8') or two 17-40 W (2'-4') T8, T9, T10 or T12 lamps; or one 18-55 W or two 18-39 W (4-pin) long compacts	ELC; Suitable for damp locations and sealed & gasketed fixtures; UL Listed
BDL60U	1 or 2 lamps	300 - 700 lm	One 17-215 W (2'-8') or two 17-40 W (2'-4') T8, T9, T10 or T12 lamps; or one 18-40 W (4-pin) long compact	Suitable for damp locations and sealed & gasketed fixtures; UL Listed
B60LPU	1 or 2 lamps	350 - 700 lm	One 17-215 W (2'-8') or two 17-40 W (2'-4') T8, T9, T10 or T12 lamps; or one 18-40 W (4-pin) long compact	ELC; Suitable for damp locations and sealed & gasketed fixtures; Low-Profile; UL Listed
BHD55U	1 lamp	700 - 1200 lm	One 14 -54 W (2'-4') T5 bipin, 22-40 W T5 circular, 36-55 W (4-pin) long compact or 17-55 W (2'-5') T8 bipin	ELC; Suitable for damp locations and sealed & gasketed fixtures; For use in Class 1, Division II type fixtures; UL Component Recognized
BHD65U	1 or 2 lamps	300 - 700 lm	One 17-215 W (2'-8') or two 17-40 W (2'-4') T8, T9, T10 or T12 lamps; or one 18-39 W long compact. Two-hour operation with one 32 W T8	Two-hour runtime; Suitable for damp locations and sealed & gasketed fixtures; For use in Class 1, Division II type fixtures; UL Component Recognized

* ELC products have a patented circuit that delays the AC ballast operation for approximately 3 seconds to prevent false tripping of the AC ballast end-of-lamp-life shutdown circuits.